

Infinity HT6000™ Series

HT6000 CO2 Laser Marker



L e a d e r I n L a s e r S o l u t i o n s

Features:

Wavelength: 10.6 um

High Speed Marking

Small Footprint

Low Maintenance

Compact Size

Excellent Marking Quality & Reliability

Laser Applications for:

✓ Marking

✓ Cutting

✓ Trimming



HYPERTRONICS PTE LTD

1 Kaki Bukit Road 1 #03-09 Enterprise One Singapore 415934

T: (65) 6280 0055 F: (65) 6284 9910 E: mail@hylax.com W: www.hylax.com

Overseas Support Centres: India T: (91) 22 3247 1150, Malaysia T: (60) 4646 6118, Thailand T: (66) 2347 8643, China T: (86) 512 6667 9226, Taiwan T: (886) 2 2234 1902

Infinity HT6000 Series

HT6000 CO2 Laser Marker



Technical Specifications

CO2 Laser	
Wavelength (um)	10.6
Output Power (W)	10 *
Pulse Repetition (kHz)	5 to 20
Pulse to Pulse Stability (%)	< 5
Input Power (kw)	1
* Other output power available up to 100W	
HyScan 200: Scanhead System	
Laser Beam Delivery:	Galvanometer Scanhead System
F-Theta Lens Marking Area (mm)	50 x 50 *
* Optional at 35 x 35, 70 x 70, 110 x 110, 140 x 140	
Utilities and Environment	
Power Supply:	230 VAC, Single Phase, 13 Amp
Operating Conditions	
Environment:	Area Under Ambient temperature without condensation
Temperature:	22 to 28 degree celsius (Optimum) 10 to 30 degree celsius (Normal)
Humidity:	Up to 70% RH maximum (Optimum & Normal)
Storage Conditions	
Environment:	Area without Condensation
Temperature:	5 to 45 degree celsius
Humidity:	Up to 75% RH maximum
Dimension	
664 mm (Length) x 130 mm (Width) x 150 mm (Height)	

Lens for Field Size (mm)	Working Distance (mm)
35 x 35	141
50 x 50	65
70 x 70	127*/146
110 x 110	165
140 x 140	215/277*

* Type D

Note: The table above indicates one selection only that must be fixed at time of purchase.



PC Controller

Type of Controller: Windows based PC Controller
 Marking Software: Hypermark CAD Based, GUI marking software for creation and editing of marking layout. Text, Barcode, Data Matrix polygon creation within few mouse clicks

Optional features includes:

- Windows True Font
- Font Editor
- PLT, AutoCAD format import
- RS – 232 Serial Comm.
- TCP/ IP comm. Via Win Socket
- BMP / Tiff marking

Options:

- Integrated Vision Inspection System
- Automatic & Semi-Auto Handlers
- Data Matrix and Linear Barcode Verifier
- Dust Collector / Fume Extractor
- Red Targeting Laser
- Auto Power Calibration System
- Marking Software Customization

Hypertronics Pte Ltd



Warranty

Hypertronics warrants each laser system to be free of material and manufacturing defects for a period of 1 year after shipment based upon normal equipment use as specified by Hypertronics and its personnel.

Legal Notices

Due to continuous improvements, all product information are subjected to change without notice. Hylax logo are trademarks of Hypertronics Pte Ltd. All rights reserved.